

RECEIVED
CENTRAL FAX CENTER

JUN 25 2007

LISTING OF CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Original) An ultrasonic puncture needle comprising:

a sheath which is inserted into a treatment tool insertion channel of an ultrasonic endoscope; and

a needle tube for being inserted into tissue within the body cavity through the sheath, which includes a plurality of staggered-array doughnut-shaped recesses over a predetermined range on the surface of the tip portion of the needle tube from the portion near the tip of the needle tube.

2. (Original) An ultrasonic puncture needle according to Claim 1, wherein the plurality of doughnut-shaped recesses are arrayed so as to be spread in a radial pattern from the tip of the needle tube.

3. (Original) An ultrasonic puncture needle according to Claim 1, wherein the multiple doughnut-shaped recesses are formed using a laser apparatus or an electric discharge machining apparatus.

4. (Currently Amended) An ultrasonic puncture needle according to Claim 3, wherein the multiple doughnut-shaped recesses are formed using a laser apparatus or an electric discharge machining apparatus under positioning control set so that the doughnut-shaped recesses have no adverse effects on [[an]] a cutting-tip portion forming the needle tube due to overlap of the doughnut-shaped recesses and the cutting-tip portion.

5. (Currently Amended) An ultrasonic puncture needle comprising
a needle tube which is to be inserted into a treatment tool insertion channel of an
ultrasonic endoscope so as to be inserted into tissue within the body cavity,
wherein the needle tube includes a plurality of donut-shaped recesses over a
predetermined range on the surface of the tip portion thereof from the tip thereof on the back side
of ~~[[an]]~~ a cutting-tip portion.
6. (Original) An ultrasonic puncture needle according to Claim 5, wherein the plurality of
recesses are arrayed so as to be spread in a radial pattern from the tip of the needle tube.
7. (Original) An ultrasonic puncture needle according to Claim 5, wherein the plurality of
recesses are formed at positions such that overlap of the recesses and the cutting-tip portion does
not occur.
8. (Original) An ultrasonic puncture needle according to Claim 6, wherein the plurality of
recesses are formed at positions such that overlap of the recesses and the cutting-tip portion does
not occur.
9. (Original) An ultrasonic puncture needle according to Claim 5, wherein the plurality of
recesses are formed in a doughnut shape using a laser apparatus or an electric discharge
machining apparatus.
10. (Original) An ultrasonic puncture needle according to Claim 6, wherein the plurality of
recesses are formed in a doughnut shape using a laser apparatus or an electric discharge
machining apparatus.

11. (Original) An ultrasonic puncture needle according to Claim 7, wherein the plurality of recesses are formed in a doughnut shape using a laser apparatus or an electric discharge machining apparatus.

12. (Currently Amended) An ultrasonic puncture needle comprising:

a puncturing portion formed with a suitable length at the tip of the ultrasonic puncture needle; and

a tube portion formed in the shape of a tube at the rear end of the puncturing portion, wherein the puncturing portion is formed of ~~[[an]]~~ a cutting-tip portion and a tube-shaped portion formed as an extension of the tube portion, which includes a plurality of donut-shaped recesses ~~ultrasonic-reflection means~~ on the surface of the tip portion thereof.

13. (Currently Amended) An ultrasonic puncture needle according to Claim 12, wherein the ~~ultrasonic-reflection means comprises~~ a plurality of doughnut-shaped recesses are formed and arrayed so as to be spread over a predetermined range on the surface of the tip portion in a radial pattern from the tip of the tube portion on the back side of the cutting-tip portion.

14. (Original) An ultrasonic puncture needle according to Claim 13, wherein the plurality of doughnut-shaped recesses are formed using a laser apparatus or an electric discharge machining apparatus.

15. (Original) An ultrasonic puncture needle according to Claim 14, wherein the plurality of doughnut-shaped recesses are formed at positions such that overlap of the recesses and the cutting-tip portion forming the needle tube does not occur, using a laser apparatus or an electric discharge machining apparatus.

16. (Original) An ultrasonic puncture needle according to Claim 12, wherein the ultrasonic-reflection means comprises a plurality of recessed portions formed and arrayed so as to be spread in a predetermined range on the surface of the tip portion in a radial pattern from the tip of the tube portion on the back side of the cutting-tip portion.

17. (Original) An ultrasonic puncture needle according to Claim 16, wherein the plurality of recessed portions are formed at positions such that overlap of the recessed portions and the cutting-tip portion does not occur.

18. (Original) An ultrasonic puncture needle according to Claim 16, wherein the plurality of recessed portions are formed in a doughnut shape using a laser apparatus or an electric discharge machining apparatus.

19. (Original) An ultrasonic puncture needle according to Claim 17, wherein the plurality of recessed portions are formed in a doughnut shape using a laser apparatus or an electric discharge machining apparatus.